



Solenoid valve VUVS-L25-M52-AD-G14-F8-1C1

Part number: 575503

FESTO



[PDF General operating conditions](#)

[→ Support Portal](#)

Datasheet product reliability

The information in this "Product reliability data sheet" is based on products being used as intended. This includes complying with all specifications in data sheets, catalogues, user documentation and the general operating conditions. The user alone is responsible for determining whether a product is suitable for a particular application.

| Feature | Value |
|---|--|
| Relevant basic safety principles ¹⁾ | Yes |
| Relevant well-tried safety principles ²⁾ | Yes |
| Service-life value B ₁₀ ³⁾ | 10 Mio cycles |
| Service-life value B10D ⁴⁾ | 20 Mio cycles |
| Fault exclusion | Bursting of the valve housing: externally directed failure of the material structure with a sudden release of the medium and associated pressure drop (according to ISO 5598, 3.2.85). |
| Design characteristics | Pneumatic spring return Supply air via duct 1 Pneumatic spring return |
| Lap | Overlap |
| Vibration resistance | Transport application test with severity level 2 in accordance with FN942017-4 and EN 60068-2-6 |
| Shock resistance | Shock test with severity level 2 in accordance with FN 942017-5 and EN 60068-2-27 |
| Max. positive test pulse with 0 signal | 2,000 µs |
| Max. negative test pulse with 1 signal | 3,600 µs |

- 1) The product-relevant basic safety principles are fulfilled according to the ISO 13849-2.
- 2) The product-relevant well-tried safety principles are fulfilled according to the ISO 13849-2.
- 3) The ascertainment of characteristic service life values is generally based on the ISO 19973 "Pneumatic fluid power - Assessment of component reliability by testing".
- 4) B10D value determined on the basis of ISO 13849-1: e.g. B10D=2*B10. Whether this value is suitable for a specific application must be checked and confirmed by the user.