

5335 1/2" PLASTIC CASE AIR IMPACT WRENCH (800LB)

1/2" 塑鋼柄氣動扳手(800LB)

- Max torque: 800 ft/lb
- Free speed: 6800 rpm
- Air consumption: 5.3 cfm
- Air inlet: 1/4"
- Overall length: 170mm
- Weight: 1.89 kgs



3834 1/2" ULTRA DUTY COMPOSITE AIR IMPACT WRENCH (1100LB)

1/2" 塑鋼柄氣動扳手(1100LB)

- Max Torque: over 1,100 ft-lb (1,486 Nm).
- Working Torque: 250~600 ft-lb (338~810 Nm).
- Blow per Min.: 1,250.
- No-load speed: 8,000 RPM +/- 10%.
- Recommend air pressure: 90 PSI (6.35 kgs).
- Air Inlet: 1/4" PT.
- Min. Hose Size: 3/8"(10 mm) I.D.
- Overall Length: 7.3"(186 mm).
- Weight: 4.4 LBS (2 kgs).



5818 3/4" HEAVY DUTY COMPOSITE AIR IMPACT WRENCH

3/4" 塑鋼柄氣動扳手(強力型)

- Bolt capacity: 1-1/8" (28mm).
- Max torque: 1200 ft / lb (1630N-M).
- Free speed: 5500 rpm.
- Air consumption: 14 cfm.
- Air inlet: 3/8".
- Air pressure: 90 psi.
- Overall length: 221mm.
- Net weight: 3.6 kg.
- Clutch mechanism: Twin Hammer.



5304 1" SMALL AIR IMPACT WRENCH

1" 槍型氣動扳手(小型)

- Bolt capacity: 1-5/8".
- Max torque: 1,700 ft/lb.
- Net weight: 5.1 kg.
- Length: 222mm.
- Air Consumption: 0.32 m³/min.
- Air Inlet: 3/8" inch.
- Vibration: 6.1 m/g².
- Speed: 4,500 RPM.
- Mechanism: twin hammer.



5813 1" AIR IMPACT WRENCH

1" 槍型氣動扳手

- Bolt capacity: 2" (50mm).
- Max torque: 2500 ft / lb (3390N-M).
- Free speed: 3400 rpm.
- Air consumption: 19.7 cfm.
- Air inlet: 3/8".
- Air pressure: 90 psi.
- Overall length: 302 mm.
- Net weight: 11.8 kg.
- Clutch mechanism: Twin Hammer.

