

Lembar data produk

Spesifikasi



auxiliary contact - 1 OC or 1 SD or 1
SDE or 1 SDV low level

29452

Main

Product or component type	Auxiliary contact
Device short name	SD SDV OF SDE
Device application	Breaker status monitoring
Range compatibility	ComPact ComPact NS630b...1600 ComPact ComPact NS1600b...3200 ComPact ComPacT INS ComPact Compact INV ComPact ComPact NSX EasyPact EasyPact CVS PowerPact PowerPact Multistandard ComPact ComPact NSX DC
Signal contacts composition	1 NO/NC
Range compatibility	Galaxy PX Galaxy VL Galaxy VM Galaxy VS Galaxy VX

Complementary

Fault type	General electric fault
Local signalling	ON/OFF indication for open/close Trip indicator for relay trip indicator Fault trip for electrical fault
Auxiliary contacts type	Low level
Mounting mode	Con clip
[Ith] conventional free air thermal current	5 A

Disklaimer: Dokumentasi ini tidak ditujukan sebagai pengganti dan tidak untuk digunakan untuk menentukan kesesuaian atau keandalan produk ini untuk aplikasi pengguna

Breaking capacity (A)	AC-12: 5 A at 24 V CA 50/60 Hz AC-12: 5 A at 48 V CA 50/60 Hz AC-12: 5 A at 110 V CA 50/60 Hz AC-12: 5 A at 220/240 V CA 50/60 Hz AC-12: 5 A at 380/440 V CA 50/60 Hz AC-12: 5 A at 480 V CA 50/60 Hz AC-15: 3 A at 24 V CA 50/60 Hz AC-15: 3 A at 48 V CA 50/60 Hz AC-15: 2.5 A at 110 V CA 50/60 Hz AC-15: 2 A at 220/240 V CA 50/60 Hz AC-15: 1.5 A at 380/440 V CA 50/60 Hz AC-15: 1 A at 480 V CA 50/60 Hz DC-12: 5 A at 24 V CC DC-12: 2.5 A at 48 V CC DC-12: 0.6 A at 110 V CC DC-12: 0.3 A at 250 V CC DC-14: 1 A at 24 V CC DC-14: 0.2 A at 48 V CC DC-14: 0.05 A at 110 V CC DC-14: 0.03 A at 250 V CC
Minimum load	1 mA at 4 V CC
Accessory / separate part category	Spare part for Compact NS630b...1600 Spare part for Compact NS1600b...3200

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.400 cm
Package 1 Width	7.800 cm
Package 1 Length	6.000 cm
Package 1 Weight	22.000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	5.000 cm
Package 2 Width	14.500 cm
Package 2 Length	17.000 cm
Package 2 Weight	228.200 g
Unit Type of Package 3	S02
Number of Units in Package 3	100
Package 3 Height	15.000 cm
Package 3 Width	30.000 cm
Package 3 Length	40.000 cm
Package 3 Weight	2.500 kg

Contractual warranty

Warranty	12 months
----------	-----------

Environmental Data

Schneider Electric bertujuan untuk mencapai status Net Zero pada tahun 2050 melalui kemitraan rantai pasokan, bahan baku yang lebih rendah, dan beredar melalui kampanye "Use Better, Use Longer, Use Again" untuk memperpanjang masa pakai dan daur ulang produk.

Environmental Data dijelaskan >

Bagaimana kami menilai keberlanjutan produk >

Jejak lingkungan	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	16
Environmental Disclosure	Product Environmental Profile

Use Better

Bahan dan Pengemasan	
Recycled metal content at CR level	0
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	REACH Declaration
Halogen content performance	Product contains halogen above thresholds
PVC free	Yes

Use Again

Repak dan remanufaktur	
Circularity Profile	No need of specific recycling operations
Take-back	No
WEEE	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins