

# GPE 60X12 SR/R CUS - Engraving material



0824430

<https://www.phoenixcontact.com/pc/products/0824430>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Engraving material, can be ordered: by sheet, silver, labeled according to customer specifications, mounting type: adhesive, lettering field size: 60 x 12 mm, Number of individual labels: 21

## Your advantages

- Labeling service: Phoenix Contact can custom-label all GPE ... markers according to your requirements
- The adhesive foil used ensures good adhesive properties, even on uneven surfaces
- Two-layer material
- The label sheet consists of prefabricated, individual self-adhesive labels

## Commercial data

Item number	0824430
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Product key	BG8145
Catalog page	Page 294 (C-5-2013)
GTIN	4046356353007
Weight per piece (including packing)	21.69 g
Weight per piece (excluding packing)	21.5 g
Customs tariff number	39203000
Country of origin	PL

# GPE 60X12 SR/R CUS - Engraving material



0824430

<https://www.phoenixcontact.com/pc/products/0824430>

## Technical data

### Product properties

Product type	Labeled device marker
Marking	
Number of individual labels	21
Number of individual labels per row	7
Marking technology	
Device	5144615 CMS-P1-PLOTTER
	5145546 P1 ENGRAVING UNIT
Printability	Engraving
	Plotter

### Environmental and real-life conditions

Ambient conditions	
Ambient temperature (operation)	-20 °C ... 85 °C
Recommended storage conditions	20°C/50% relative humidity. Storage in the original packaging is recommended.
Recommended ambient temperature (storage/transport)	20 °C
Recommended humidity (storage/transport)	50 %
Shelf life	12 months

### Mounting

Mounting type	adhesive
---------------	----------

### Material specifications

Adhesive strength	50 µm
Adhesive	Acrylic
Color	silver
Material	TRANSPLY-ABS
Components	free from silicone and halogen

### Environmental and real-life conditions

Ambient conditions	
Ambient temperature (operation)	-20 °C ... 85 °C
Recommended storage conditions	20°C/50% relative humidity. Storage in the original packaging is recommended.
Recommended ambient temperature (storage/transport)	20 °C
Recommended humidity (storage/transport)	50 %
Shelf life	12 months

### Dimensions

# GPE 60X12 SR/R CUS - Engraving material



0824430

<https://www.phoenixcontact.com/pc/products/0824430>

Width	60 mm
Length	12 mm
Material strength	0.80 mm

## Standards and regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
-----------------	-----------------------------

# GPE 60X12 SR/R CUS - Engraving material



0824430

<https://www.phoenixcontact.com/pc/products/0824430>

## Classifications

### ECLASS

ECLASS-11.0	27281103
ECLASS-12.0	27281103
ECLASS-13.0	27281103

### ETIM

ETIM 8.0	EC001288
----------	----------

### UNSPSC

UNSPSC 21.0	39131500
-------------	----------

Phoenix Contact 2023 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG

Flachsmarktstraße 8

D-32825 Blomberg

+49 (0) 5235-3 00

[info@phoenixcontact.com](mailto:info@phoenixcontact.com)