



## Main

Range of product	Acti 9
Product name	Acti 9 iRO
Product or component type	Buzzer
Device short name	IRO

## Complementary

[Us] rated supply voltage	230 V AC 50/60 Hz
Power consumption in VA	5 VA
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	2
Height	81 mm
Width	18 mm
Depth	72 mm
Product weight	64 g
Colour	White
Auxiliary connection terminal	Tunnel type terminals rigid < 4 mm <sup>2</sup> Tunnel type terminals flexible < 4 mm <sup>2</sup> Tunnel type terminals flexible with ferrule < 4 mm <sup>2</sup>
Wire stripping length	12 mm (bottom)
Tightening torque	1.3 N.m

## Environment

Noise level	70 dB
Type of sound	Buzzer
IP degree of protection	IP40 (in modular enclosure) conforming to IEC 60529 IP20 conforming to IEC 60529
Ambient air temperature for operation	-10...40 °C
Ambient air temperature for storage	-25...60 °C

## Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0627 - Schneider Electric declaration of conformity
------------------------	---

REACH

Reference not containing SVHC above the threshold  
Reference not containing SVHC above the threshold

## Contractual warranty

Warranty period

18 months