





## $B\Omega SS^{\circ}$

## COLOURS CHOICE

## **PIPING SYSTEM**



All  $B\Omega SS$  Rigid PVC Conduit and Fittings are manufactured in strict accordance with the British Standard BSEN 61386 - 21:2004/ IEC 61386-21:2002 Fire Retardant and High Impact Polyvinyl Chloride is used to manufactured the conduit and Fittings.

Standard colours | Scan QR Code












DESCRIPTION	WE	BK	ORDER NO.
JUNCTION BOXES 20 mm			with lids & screw
1 way	0	•	B240/20/1
2 way	0	•	B240/20/2
2 way angle	0	•	B240/20/2A
3 way	0	•	B240/20/3
4 way	0	•	B240/20/4
JUNCTION BOXES 25 mm			with lids & screw
1 way	0	•	B240/25/1
2 way	0	•	B240/25/2
2 way angle	0	•	B240/25/2A
3 way	0	•	B240/25/3
4 way	0	•	B240/25/4



	ONDER NO.	WE DR	DESCRIPTIO
	CONDUIT		
	B9016	0	16 mm
	B9020	0	20 mm
	B9025	0	25 mm
6	B9032	0	32 mm
	CORRUGATER	CONDUIT	

## CORRUGATED CONDUIT B9016 CM 16 mm B9020 CM 20 mm B9025 CM 25 mm B9032 CM 32 mm

JOINING COU	PLING	
B242/16	0	16 mm
B242/20	0	20 mm
B242/25	0	25 mm
B242/32	0	32 mm





90° BENDS		
B247/16	0	16 mm
B247/20	0	20 mm
B247/25	0	25 mm
B247/32	0	32 mm

20mm

20 mm

25 mm

32 mm

		SADDLE
0	0	B261/20 B261/25 B261/32
0	0	SPACER
		D261 C

U			
0	SPACER		
	B261 S	0	All size

	CONDUIT CLIP		
1	B280/16	0	16 mm
11	B280/20	0	20 mm
	B280/25	0	25 mm
	B280/32	0	32 mm

<b>SCREWED COUP</b>	LING		
B258/16	0	•	16 mm
B258/20	0	•	20 mm
B258/25	0	•	25 mm
B258/32	0	•	32 mm
MAIFRUSHES			

_	MALE BUSHES			
	B281/16	0	•	16 mm
	B281/20	0	•	20 mm
	B281/25	0	•	25 mm
	B281/32	0	•	32 mm
1	GLANDS			





DECEDIBLION	ODDED NO	חח	OB	VIA	CD	DI
DESCRIPTION	ORDER NO.	RD	OR	YW	GR	BL
LIDS JUNCTION	N BOXES					
B240L		•	•	•	•	•
JUNCTION BOX	ES 20 mm			with I	ids &	screw
1 way	B240/20/1					
2 way	B240/20/2	•		•	•	•
2 way angle	B240/20/2A					
3 way	B240/20/3	•	•		•	
4 way	B240/20/4					
,						

<sup>\*</sup> Minimum Quantity may apply. Custom colour are available upon request.
\*\* The colours shown above are simulated colour. The actual colour may differ,



ORDER NO.	RD	OR	YW	GR	BL
CONDUIT 20 mm					
39020	•	•	•	•	•
CORRUGATED CONDUIT 20 mm					
39020 CM	•	•	•	•	•
OINING COUPLING 20 mm					
3242/ 20	•	•	•	•	•
SADDLE 20 mm					
3261/20	•	•	•	•	

please contact our marketing for a colour sample and availability.