

Optional Accessories



Article No.	Description
KW1800890	Turbo/Rotating Nozzles 3.0 SQ/4"
KW1800893	Water Filter Clear Bowl 1/2" BSP
10059967	6 in 1 Changeover Nozzle
10059969	Pivoting Coupler
KW1800891	Foam Generator SQ 1/4"
KW1800899	Bend Lance SQ1/4" M22 Male 20"
KW1800897	Short Gun with 5" Lance
KW1800894	HP Gun for KW1800732 WPG02 3600Psi

Article No.	Description
KW1800895	HP Gun for KW1800728 WPG04 4000Psi
KW1800896	HP Gun for KW1800729/730 WPG05 5000Psi
KW1800885	Nozzle Tip 3.0 for KW1800728/732
KW1800898	Straight Lance for KW1800728/730 SLA01
KW1800901	Hose 4350Psi SQ3/8IN Plug for KW1800729/730
KW1800900	Hose 3600Psi SQ3/8IN Plug for KW1800728/732
10059968	Stainless Steel Surface Cleaner 21"

HOT WATER HIGH PRESSURE



HEATER INSIDE
PATENTED EMF SYSTEM
Made in USA



**REDUCE CLEANING TIME
UP TO 40%**




Accessories Included:



High Quality
Fuel Filter




Heavy Duty
quad-ruplex
cogged belt drive
system, with
self-tight device to
prevent slippage



Energy efficient
top fired powder
coated heat
exchanger

EMF (Electro Magnetic
Firing System)



Triple Air Flow



Article No.	10029178
Description	Hot and Cold High Pressure Cleaner 172 bar with Gasoline Engine 6.5HP
Specification	
Max Head Pressure (PSI/bar)	2500/172
Water Flow Rate (gpm/lpm)	3.3 /12.6
Outlet Water Temperature	66 °C/150 °rise above inlet ambient (93 °C/200 °F maximum)
Horse Power/Displacement (HP/cc)	6.5 HP / 196 cc
Fuel Tank Capacity (ℓ)	3.6 L
Fuel Capacity (ℓ)	15 Liter (4 Gallon)
Fuel Consumption(lph)	5.8 lph (1.58 gph)
Emf Device	Patented Electro Magnetic Firing (EMF) System
Heat Exchanger	Vertical, Top Fired, Dual Spiral Coil
Fuel Filter / Water Separator	Spin on (10micron) filter / E-Z water drain
Pressure Switch	Shutt off burner fuel supply upon trigger release
High Limit Switch	Shut off burner fuel supply when outlet water temperature exceeds 200 °F / 93 °C
Pump Thermal Protection	Protect pump from over heat when in by pass mode, activates at 60 °C / 140 °F
Accessories Included	Hot water grade professional trigger gun, insulated dual lance, fixed nozzle, hot water pressure hose
Dimension (mm)	850 x 700 x 1000
Weight (Kg)	110