

E8431RJ_6_SZ

ZENCELO 1 Gang Data Outlet Category 6e with Integrated Shutter, Silver Bronze



Main

Range of product	ZENcelo
Range	ZENcelo
Product or component type	Data socket
Device application	Communication
Colour tint	Silver bronze

Complementary

Rated current	1.5 A
Communication network category	Data : 6e
Insulation resistance	≥ 200 MOhm
Contact resistance	≤ 1 μ Ohm
Number of gangs	1 gang
Return loss	≥ 23 dB
AWG gauge	AWG 26...AWG 22 for 4 twisted pair cables
Contacts material	Phosphor bronze with gold plating for contact Phosphor bronze with nickel plating for IDC contact PC for housing
Material	Polycarbonate plastic part
Device mounting	Flush Surface
Width	87 mm
Height	87 mm
Depth	36 mm

Environment

Dielectric strength	1000 V for 60 s at 60 Hz
Ambient air temperature for operation	1...35 °C
Relative humidity	0...95 %
Environmental characteristic	No UV resistant
Standards	TIA/EIA-568-B.2-1 ASTMD4566-98

Offer Sustainability

RoHS (date code: YYWW)	Will be compliant on 4Q2016
REACH	Reference not containing SVHC above the threshold

Product Life Status : **Commercialised**