



Main

Range	ZENcelo
Product or component-type	Message indicator
Local signalling	Indicator light neon green please clean up Indicator light neon orange do not disturb
Colour tint	Silver bronze

Complementary

Device mounting	Flush Surface
Clamping connection capacity	3 x 2.5 mm ² for solid cable(s) 3 x 2.5 mm ² for stranded cable(s) 4 x 1.5 mm ² for solid cable(s) 4 x 1.5 mm ² for stranded cable(s)
[Ue] rated operational voltage	250 V AC 50/60 Hz
Material	Brass contact Polycarbonate base Polycarbonate cover Polycarbonate grid plate Polycarbonate surround
Connections - terminals	Folded terminal illuminated indicators
Embedding depth	19.57 mm
Width	87 mm
Height	87 mm
Depth	27.72 mm

Environment

Ambient air temperature for operation	-5...35 °C
Relative humidity	0...95 %
Environmental characteristic	No UV resistant
Operating altitude	<= 2000 m
Standards	EN 60669-1 GB 16915.1 IEC 60669-1 MS IEC 60669-1

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 1301 - Schneider Electric declaration of conformity  Schneider Electric declaration of conformity
------------------------	--

Contractual warranty

Warranty period	18 months
-----------------	-----------

Product Life Status :	Commercialised
-----------------------	----------------