

SOUND LEVEL METER DIGITAL

**Features:**

- Bluetooth interface to Krisbow meter mobile app
- Max Hold and Data Hold Function
- Auto Power Off
- Easy to use, fast and accurate measurement
- Mini size with modern design outlook
- Low battery indication
- Large digital LCD display backlight

Article No.	10176592
Description	Sound Meter Digital 35 to 130 dB
Specification	
Frequency range	31.5Hz to 8KHz
Measuring level range	35 to 130 dB (auto mode)
Accuracy	± 3 dB (under reference conditions 94dB, 1KHz)
Mode Level ranges	Lo: 35-80 dB; Med: 50-100 dB; Hi: 80-130dB
Resolution	0.1dB
Frequency weighting	A and C
Microphone	½ inch condenser
Display	LCD (4 digits)
Display Update	0.5 sec.
Power supply	9V battery
Dimensions	185 x 55 x 38 mm
Weight (Net/ Gross)	153/ 290 g

SOUND LEVEL METER DATALOGGER

**Features:**

- Conforms to the IEC61672-1 class 2 for Sound Level Meter
- Comply with EMC
- Datalogger function (32700 readings)
- USB Interface to PC
- Easy to use, fast and accurate measurement
- Low battery indication
- Large digital LCD display
- Max & Min measurement
- Over-range & Under-range indication
- Adjustable alarm level

Article No.	10176566
Description	Sound Level Meter Datalogger
Specification	
Frequency range	31.5Hz to 8KHz
Measuring level range	30 to 130 dB (auto mode)
Accuracy	± 1.4 dB
Mode Level ranges	Lo: 35-80 dB; Med: 50-100 dB; Hi: 80-130dB
Resolution	0.1dB
Frequency weighting	A and C
Microphone	½ inch electric condenser
Display	LCD (4 digits)
Display Update	2 times/sec
Power supply	9V battery
Dimensions	248 x 65 x 45 mm
Weight (Net/ Gross)	248/ 350 g

LIGHT METER DIGITAL

**Features:**

- Bluetooth interface to Krisbow meter mobile app
- Max Hold and Data Hold Function
- Auto Power Off
- Easy to use, fast and accurate measurement
- Mini size with modern design outlook
- Low battery indication
- Large digital LCD display backlight

Article No.	10176593
Description	Light Meter Digital 40.000 LUX
Specification	
Measuring Range	400.0, 4000, 40.00K Lux / 40.00, 400.0, 4000 Fc Note: 1Fc = 10.76 Lux
Resolution	0.1 Lux or 0.01 Fc
Accuracy	± 5% ± 10d (<10,000 Lux) ± 10% ± 10d (>10,000 Lux)
Over Range Indication	"OL" icon
Measuring Rate	2 times / second
Repeatability	± 3%
Display	3 ¾ digit LCD w/ high speed 50 segment bar graph
Power supply	9V battery
Unit Dimension	206 x 55 x 38 mm
Weight (Net/ Gross)	140/ 275 g

LIGHT METER

**Features:**

- Easy to use with pocket size and light weight
- 3 1/2 digit LCD display with LUX, FC, MAX, hold indication
- Accurate display light level in terms of foot candles (fc) or lux over wide range
- Measures from 0 to 50000 Lux / Fc in four range with resolution 0.1 Lux/Fc
- Max. hold and data hold
- Auto power off
- Photo detector dimensions: 115 x 60 x 27mm

CE EMC
EN : 61326
Accessories:
Box carrying case

Article No.	KW0600288
Description	Light Meter
Specification	
Measuring Range	200, 2000, 20000, 50000Lux/fc
Accuracy	±5% rdg ±10 dgt (<10,000 Lux/fc) ±10% rdg ±10 dgt (>10,000Lux/fc)
(Calibrated to Standard Incandescent Lamp 2856K)	
Dimensions ((HxWxD) cm)	18.8 x 6.45 x 2.45
Weight (kg)	0.16