

PT. NACHINDO TAPE INDUSTRY

Desa Betro, Kecamatan Sedati, Sidoarjo - 61253, Indonesia Telp.: 062 - 031 - 8910285 (Hunting), Fax.: 062 - 031 - 8910295 P.O.Box 1517 Surabaya - 60015, Indonesia

TECHNICAL DATA SHEET

PRODUCT NAME : Mending Tape Nachi

PRODUCT COLOR : Transparant (Easy Tear)

FEATURES

Mending tape is invisible adhesive tape made from BOPP film and waterbase adhesive, Mending tape is easy tear.

TECHNICAL CHARACTERISTICS:

PEEL ADHESION TO STEEL	Breaking strength (MD)	Elongation at break (MD)	TOTAL THICKNESS
PSTC-101:2007	PSTC-131:2007	PSTC-131:2007	PSTC-133:2007
(N /25.4mm)	(N/25.4mm)	(%)	(micron)
MIN 4.000	MIN 19.600	Less than 100	53 ± 2

APPLICATION:

- Repairing tears in book or document
- Splicing

STORAGE AND USAGE CONDITION

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight. Surface to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

LAB TEST CONDITION

Temperature : $23^{\circ}\text{C} \pm 1^{\circ}\text{C}$ Humidity : $50 \% \pm 5 \% \text{ RH}$

NOTE

The physical and performance characteristic shown are averages obtained from tests recommended by PSTC or our procedure. A particular roll may vary slightly from these averages and it is recommended that the buyer determine the suitability for his own purposes.