

PRODUCT-DETAILS

## B23 312-100 B23 312-100, Energy meter'Silver', Modbus RS485, Three-phase, 5 A



General Information	
Extended Product Type	B23 312-100
Product ID	2CMA100169R1000
ABB Type Designation	B23 312-100
EAN	7392696001694
Catalog Description	B23 312-100, Energy meter'Silver', Modbus RS485, Three-phase, 5 A
Long Description	Advanced compact DIN-rail meter with an easy to read back lighted display. The meter is intended for use in the commercial or residential buildings etc. The meter can be used in 3 or 4 wire systems. The meter has several instrumentation values, 25 possible alarms and event logs. Three phase direct connected for active and reactive energy. Import and export of energy in different registers and one total. Resettable register for intermediate values. Up to four tariffs. Two outputs and inputs for pulses or alarm etc. RS-485 communication over Modbus RTU or EQ Bus. Accuracy class 1.0 (or B for MID meters). The meters is IEC approved + MID approved and verified.

Eco Transparency	
Environmental Product Declaration - EPD	9AKK108467A4138

Technical	
Standards	IEC 62052-11

B23 312-100 2

Function	Electricity meter
Sub-Function	Silver
Rated Voltage (U <sub>r</sub> )	3x220-240 V
Voltage Range	3x176276 V
Rated Current (I <sub>n</sub> )	5 A Maximum 65 A
Current Rating	5 A
Rated Frequency (f)	50 / 60 Hz
	0.721 W
Communication Interface	Modbus RS485
Accuracy	Active Energy Class B MID (±1%)
Measuring Instrument Conformity	Measurement Instrument Directive (MID)
Meter Tariff Control	External
Meter Tariff Rating	Multi-Tariff
Pulse Output Rate	1-999999
Number of Poles	4
Number of Phases	Three-phase
Number of Counter Positions	7
Number of Digital In/Outputs	2 DI 2 DO
Meter Type	Direct connected
Mounting Type	DIN-Rail
Pulse Output Type	Electrical
Type of Indicator	Digital
Enclosure Material	Polycarbonate in transparent front glass. Glass reinforced polycarbonate in bottom case and upper case. Polycarbonate in terminal cover.
I/O Option	2 digital output, 2 digital input
Communication	Modbus RTU
Connecting Capacity Main Circuit	1 25 mm²

Environmental	
Ambient Air Temperature	Operation -40 70 °C
Degree of Protection	IP20
RoHS Status	Following EU Directive 2002/95/EC August 18, 2005 and amendment
RoHS Information	2CMC485006
Environmental Information	2CMC485003D0001
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Dimensions	
Width in Number of Modular Spacings	4
Product Net Width	70 mm
Product Net Height	26.5 mm
Product Net Depth / Length	65 mm
Product Net Weight	0.34 kg

B23 312-100 3

Size 96X70X65

Ordering	
Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	0.41 kg
E-Number (Finland)	6625038
E-Number (Sweden)	0900041

#### Certificates and Declarations

Declaration of Conformity 2CMC485001D0001 - CE

#### Installation

Instructions and Manuals 2CMC485019M0201

#### Popular Downloads

Data Sheet, Technical 2CMC485003M0201 Information 2CMC485003M0201

# Classifications ETIM 8 ETIM 9

ETIM 9 EC001506 - Kilowatt-hour meter
WEEE Category 5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B Business To Consumer
CN8 90283019

 eClass
 V11.0 : 27142316

 Object Classification Code
 P

#### Accessories

Identifier	Description	Туре	Quantity	Unit Of Measure
2CCG000242R0001	SCU100 Control unit	SCU100	1	piece
2CDG110226R0011	QA/S3.16.1 Energy Analyzer, M-Bus, 16 Devices, MDRC	QA/S3.16.1	1	piece
2CDG110227R0011	QA/S3.64.1 Energy Analyzer, M-Bus, 64 Devices, MDRC	QA/S3.64.1	1	piece
2CDG110228R0011	QA/S4.16.1 Energy Analyzer, Modbus RTU, 16 Devices, MDRC	QA/S4.16.1	1	piece
2CDG110229R0011	QA/S4.64.1 Energy Analyzer, Modbus RTU, 64 Devices, MDRC	QA/S4.64.1	1	piece
2CDG110224R0011	QA/S1.16.1 Energy Analyzer, KNX, 16 Devices, MDRC	QA/S1.16.1	1	piece

EC001506 - Kilowatt-hour meter

B23 312-100 4

### Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Modular\ DIN\ Rail\ Products \rightarrow Energy\ Efficiency\ Devices \rightarrow Energy\ Meters$ 





