

PosiTest[®] DFT

Coating Thickness Gage

Ideal for...

- Powder Coaters
- Paint Applicators
- Coating Inspectors
- Painting Contractors
- Automotive Refinishers

2 Models...

Ferrous for STEEL

Combo for ALL METALS



simply
measures

PosiTest® DFT

Coating Thickness Gage

Two Models

- **PosiTest DFT Ferrous**
measures non-magnetic coatings on steel.
- **PosiTest DFT Combo**
measures both non-magnetic coatings on steel
AND non-conductive coatings on aluminum,
brass, etc. **Automatically** recognizes the
substrate and takes a measurement.



Features

- Fast, repeatable measurements
- No calibration required for most applications
- ZERO feature for rough or curved surfaces
- Handy RESET feature when no zero reference is available
- Strong, wear-resistant, ruby-tipped probe
- Unique FLIP Display enables right-side-up viewing in any position
- Audible and visible measurement indication
- V-groove in probe for positioning on cylindrical parts
- Mils/Microns switchable
- Basic instructions on the back of each gage
- Built-in wrist strap for added convenience and safety
- 2 Year Warranty

Specifications

Measurement Range	0 – 40 mils	0 – 1000 µm
Accuracy	±(0.1 mils + 3%)	±(2µm + 3%)
Size	4 x 1.5 x 0.9 in.	100 x 38 x 23 mm
Weight	2.5 oz.	70 g



Unique FLIP Display
enables right-side-up
viewing in any position



Gage Comes Complete with built-in probe,
wrist strap, plastic shims, hard shell storage case,
AAA battery, instructions and two (2) year warranty.

Conforms to: ISO 2178/2360/2808,
prEN ISO 19840, ASTM B244/B499/B659/D1186/D1400/D7091/E376/G12,
BS3900-C5, SSPC-PA2 and others. *Certificate of Calibration traceable to NIST available.*

© DeFelsko Corporation USA 2008. All Rights Reserved. Technical Data subject to change without notice. U.S. Patent # Re.35,703 • Printed in U.S.A. PDFDT.v/LW/W0804