

Glazing[®]

ACRYLIC SEALANT



Water Wash-up Interior or Exterior

Glazing Acrylic is a one-part paintable, water based acrylic sealant. It has good adhesion to wood, concrete, marble, glass, and most plastics materials. Suitable for interior applications.

- Paintable can be painted after 2 hours
- Fast Drying
- Non-Staining, does not pick up dirt
- Clean up with water or damp cloth
- Excellent adhesion
- Good water resistance when cured
- Fungus and mould resistant

Typical Property Data

UNCURED PROPERTIES		
Consistency		Paste
Slump *1 (20 mm)	mm	0
Tack Free Time *1 (23°C)	min	10
Curing Time *2 (23°C, 50% RH)	day	2
CURED PROPERTIES *3 (23°C, 50% RH 3days)		
Appearance		Elastic Rubber
Density (23°C)	g/cm3	1.00
Hardness (Type A)		22
Tensile Strength	MPa	1.9
Elongation	%	500

*1 : JIS A 1439

*2 : 5mm thickness

*3 : JIS K 6249

Uses & Applications

Primerless adhesion to wood, concrete, marble, glass, window, door frames, most plastic, around ceramic tiles, cracks in plasterboard, cracks in brickwork and between light partition walls.

Packaging

Glazing Acrylic is available in 300 ml plastic caulking cartridges.

Colors

Glazing Acrylic is available in standard colors :

White and Grey

MANUFACTURED AND PACKED BY:



PT. INDO KARYA ANUGERAH
GRAHA IKA
Jl. Kaji Raya no. 28
Jakarta Pusat, Indonesia 10130
P : +62 21 632 9461
F : +62 21 633 9724
www.ika-group.com