



CD732

Digital Multimeters / Multifunction



Safety

IEC61010 CAT.II DC1000V・AC750V/CAT.III 600V

Basic Features

- 6000 count
- Use of fire-retarding materials for holster and circuit board
- Wide-range capacitance measurement (0.01nF to 3999 μ F)
- Data hold / Range hold
- Safety cap on 6•15A terminal
- Protective holster with wall hanger and lead holder
- Auto Power Save (16min.) (cancelable)

Display : numeral display 6000, bar graph 61 segments

Sampling rate : 3 times/sec., 30 times/sec. for bar graph

Optional Accessories

Clamp probe : CL-22AD, CL3000, CL33DC

HV probe : HV-60

Carrying case : C-SP

Adapter : CL-13a, CL-14, CL-15a, CL-DG3a, TL-9IC, TL-A4, TL-A7M, TL-A7M2

Specifications



CD732	Measuring range	Best accuracy	Resolution	Input impedance
DCV	600m/6/60/600/1000V	±(0.5%+2)	0.1mV	DCV: 10M~ 100MΩ
ACV	6/60/600/750V	±(1.2%+5)	0.001V	
DCA	600 μ/6000 μ/60m/600m/6/15A	±(1.5%+3)	0.1 μA	ACV: 10M~ 11MΩ
ACA	600 μ/6000 μ/60m/600m/6/15A	±(1.8%+5)	0.1 μA	
Resistance	600/6k/60k/600k/6M/60MΩ	±(1.2%+4)	0.1 Ω	
Capacitance	40n/400n/4 μ/40 μ/400 μ/4000 μF	±(5.0%+6)	0.01nF	
Frequency	9.999/99.99/999.9/9.999k/99.99kHz	±(0.5%+3)		
Duty cycle	20 ~ 80%	±(0.5%+5)		
Continuity	Buzzer sounds and LED lights up at between 10 ~ 60 Ω Open voltage : approx. 0.63V			
Diode test	Open voltage : approx. 2.7V			
Bandwidth	45~500Hz			
Fuse / Battery	0.4A/1000V 30kA ϕ 6.3X32mm 16A/1000V 30kA ϕ 10X38mm	R6×2		
Size / Mass	H167XW90XD48mm/320g (including holster)			
Standard accessories included	Test lead(TL-25a), Holster(H-70), Instruction manual			